

PERFORMANCE FEATURES

MARKET USES



X Textile Softener

Product Safety

Representative.

When considering the use of Ulterion International products, please refer to the

latest Material Safety Data Sheets (MSDS).

If you require an MSDS for this product; please call your Ulterion International

- Full, soft hand
- **Excellent drape**
- Low yellowing; little effect on shades
- Compatible with most nonionic, cationic, finishing auxiliaries
- Helps to improve wrinkle resistance, tear and tensile strength

Product Description

Ulterion® ASC is a concentrated aminofunctional cationic polymer that reacts during drying to give a durable silicone finish on fibers and fabrics. *Ulterion*® ASC is cationic in nature and can be applied by exhaust or pad applications.

Typical Properties

Appearance: Colorless to Slight Yellow;

Hazy to Translucent Liquid

Cationic Silicone Softener Type рΗ 5.0 - 7.0

Activity 58 %

Application Methods

Recommended usage level for pad application is 0.2 to 1.5% on weight of bath to provide a luxurious hand for most fabrics. Product can also be applied via exhaust methods.

Ulterion International, LLC 200 Tanner Drive Taylors, SC 29687 Phone: (864) 609-0910 Fax: (864) 331-4264 www.ulterion.com



The information contained herein is thought to be accurate in all aspects; however, the applications for these products mentioned are presented without guarantee or responsibility as to the suitability of our products whether used singly or in combination with other products. Nothing herein is to be taken as a license to operate under or as a recommendation to infringe any patents. The products are sold without warranty, expressed or implied, and are purchased at buyer's